



Benefits

Great Value!
Charges Both AA & AAA NiMH Cells
Simple and Easy to Use with Convenient Wall Plug-In

Features

LED Indicator

- Red = Charging
- Green = complete or trickle charge
- Flashing Red = error – abnormal battery or temperature

Available SKU's

- No Cells
- 2x HR6/AA (1800mAh)
- 4x HR6/AA Cells (1800mAh)
- 4x HR03/AAA Cells (900mAh)

Maintenance Charge Keeps Cells Fresh
Charges in Six Hours*

Safety

Charge Termination Based on Temperature, and/or Built-In Timer

- Over temperature shutoff – prevents overheat of cell

Design

International Charge Capability – device can be used worldwide (with suitable converter plug)

- Primary plug matches local requirements

Packaging with Clear Device Linkage, Leveraging Duracell Heritage

Technical

Battery Charger	Class 2, integral Power Supply
Plug	Direct Plug-In Matches Local Requirements
Battery Type	NiMH HR6/AA or HR03/AAA
Battery Fit	2 or 4 NiMH AA/HR6, 2 NiMH AAA/HR03
Input	100–240V AC, 50–60 Hz
Output	HR6/AA: 5.6V DC 0.36A HR03/AAA: 2.8V DC 0.16A
Operating Temperature	0° C – 40° C (32° F – 103° F)
Dimensions	120mm (L) x 80mm (W) x 34mm (H)

*Charge rate and time is dependent on cell capacity, discharge state, and operating temperature.



Berkshire Corporate Park
 Bethel, CT 06801 U.S.A.
 Telephone Toll-free:
 (Global) 1-203-796-4500
 Internet: www.duracell.com