

DURACELL®

RECHARGEABLE ACCU

1 Hour Charger

CEF80



Benefits

Charges 1 to 4 AA or AAA Cells in One Hour!*
Simple and Easy to Use

Features

Independent Channel Charging

- Four independent channels for AA with toggle switch for AAA cells
- Single cell charging capability

Four Independent Charge LED's

- Red = Charging
- LED's Off = Complete
- Flashing Red = Error – Abnormal battery or abnormal temperature

Maintenance Charge Keeps Cells Fresh

4 HR6/AA Cells Included (2300mAh)

Safety

Microprocessor Controlled

- Charge Termination based on -dV, temperature, and/or built-in timer
- Primary Cell Protection – will not charge non-rechargeable batteries
- Over-temperature shutoff – prevents overheat of cell
- Over-charge protection – prevents cell damage
- Power Protection Circuit – resets whenever battery is removed – or power is interrupted

Design

International Charge Capability – device can be used worldwide (with suitable converter plug)

- Primary plug matches local requirements

Packaging with Clear Device Linkage, Leveraging Duracell Heritage

Technical

Battery Charger

Class 2, Integral Power Supply

Plug

Direct Plug-In Matches Local Requirements

Battery Type

NiMH HR6/AA or HR03/AAA

Battery Fit

1-4 NiMH AA/HR6 or 1-4 AAA/HR03

Average Weight

143 grams (5 ounces)

Input

100-240V AC, 50-60 Hz

Output

HR6/AA: 1.4V DC 2A per slot
HR03/AAA: 1.4V DC 1.0A per slot

Operating Temperature

0° C – 40° C (32° F – 103° F)

Dimensions

150 mm (L) x 84 mm (W) x 47 mm (H)

*Charge rate and time is dependent on cell capacity, discharge state, and operating temperature.



Berkshire Corporate Park
Bethel, CT 06801 U.S.A.
Telephone Toll-free:
(Global) 1-203-796-4500
Internet: www.duracell.com