

GPL 12880

12V 88.0Ah

GPL 12880 is a general purpose battery with 10 years expected life under normal float charge. As with all CSB batteries, all are rechargeable, highly efficient, leak proof and maintenance free.




Specification

Cells Per Unit	□ □ □ □	6
Voltage Per Unit	□ □ □ □	12
Capacity	□ □ □ □	88Ah @ 20hr-rate to 1.75V per cell @25 °C (77°F)
Weight	□ □ □ □	Approx. 30kg(66.1 lbs)
Maximum Discharge Current	□ □	700A(5sec)
Internal Resistance	□ □ □ □	Approx. 6mΩ
Operating Temperature Range	□ □	Discharge: -20°C~50°C (-4°F~122°F)
	□ □	Charge: -20°C~50°C (-4°F~122°F)
	□ □	Storage: -20°C~40°C (-4°F~104°F)
Nominal Operating Temperature Range	□	25°C±3°C (77°F±5°F)
Float Charging Voltage	□ □ □ □	13.5 to 13.8 VDC/unit Average at 25°C (77°F)
Recommended Maximum Charging	□	26.4A
Current Limit		
Equalization and Cycle Service	□ □	14.4 to 15.0 VDC/unit Average at 25°C (77°F)
Self Discharge	□ □ □ □	CSB Batteries can be stored for more than 6 months at 25°C (77°F). Please charge batteries before using. For higher temperatures the time interval will be shorter.
Terminal	□ □ □ □	Thread Insert & Bolt
Container Material	□ □ □ □	-Polypropylene (UL94-HB)*Flammability resistance of UL94-V0 can be available upon request.



CSB-manufactured batteries are UL-recognized components under UL924 and UL1989. CSB is also certified by ISO 9001 and ISO 14001.

Dimensions



Constant Current Discharge Characteristics Unit:A (25°C, 77°F)


F.V/Time	5MIN	10MIN	15MIN	30MIN	1HR	2HR	3HR	4HR	5HR	8HR	10HR	20HR
1.60V	362.00	239.00	174.00	104.00	59.50	34.60	23.90	18.60	16.10	10.50	8.65	4.67
1.67V	339.50	225.50	170.50	102.50	58.80	34.20	23.70	18.50	16.00	10.40	8.59	4.64
1.70V	317.00	212.00	167.00	101.00	58.10	33.70	23.40	18.40	15.90	10.30	8.52	4.61
1.75V	281.00	195.00	158.00	95.70	56.50	33.20	23.00	18.10	15.60	10.09	8.48	4.58
1.80V	245.00	178.00	149.00	90.30	54.80	32.70	22.50	17.80	15.30	9.88	8.44	4.55
1.83V	223.40	167.80	143.60	87.10	53.80	32.40	22.20	17.60	15.10	9.75	8.42	4.53

Constant Power Discharge Characteristics Unit:W (25°C, 77°F)


F.V/Time	5MIN	10MIN	15MIN	30MIN	1HR	2HR	3HR	4HR	5HR	8HR	10HR	20HR
1.60V	3,810.00	2,640.00	1,920.00	1,190.00	694.00	405.00	282.00	219.00	189.00	124.00	105.00	59.40
1.67V	3,620.00	2,490.00	1,875.00	1,170.00	687.50	402.00	279.00	218.00	188.00	123.50	104.50	59.20
1.70V	3,430.00	2,340.00	1,830.00	1,150.00	681.00	399.00	276.00	217.00	187.00	123.00	104.00	58.90
1.75V	3,080.00	2,160.00	1,765.00	1,100.00	663.50	393.00	272.00	213.50	184.00	121.50	103.00	57.90
1.80V	2,730.00	1,980.00	1,700.00	1,050.00	646.00	387.00	268.00	210.00	181.00	120.00	102.00	56.80
1.83V	2,520.00	1,872.00	1,661.00	1,020.00	635.50	383.40	265.60	207.90	179.20	119.10	101.40	56.20

● All mentioned values are average values.


Trickle (or Float) Service Life




Capacity Retention Characteristic




Battery Voltage and Charge Time for Standby Use



Terminal Voltage (V) and Discharge Time (25°C 77°F)



Battery Voltage and Charge Time for Cycle Use



Discharge Current VS. Discharge Voltage

Final Discharge Voltage V/Cell	1.75	1.70	1.55	1.30
Discharge Current (A)	0.2C > (A)	0.2C < (A) < 0.5C	0.5C < (A) < 1.0C	(A) > 1.0C

Charging Procedures

Application	Temperature	Charge Voltage (V/Cell)		Max. Charge Current
		Set Point	Allowable Range	
Cycle Use	25°C (77°F)	2.45	2.40~2.50	0.3C
Standby	25°C (77°F)	2.275	2.25~2.30	

Sales Office URL: WWW.CSB-BATTERY.COM

CSB BATTERY CO., LTD.
TAIWAN OFFICE
Tel: +886-2-8751-5000
Fax: +886-2-8751-6161
E-mail: service@csb-battery.com

CSB BATTERY OF NETHERLANDS B.V.
NETHERLANDS OFFICE
Tel: +31(0) 180 418 140
Fax: +31(0) 180 418 327
E-mail: eurosales@csb-battery.com

CSB BATTERY (SINGAPORE) PTE., LTD.
SINGAPORE OFFICE
Tel: +65-6742-4944
Fax: +65-6742-4744
E-mail: sales@csb-battery.com

CSB BATTERY TECHNOLOGIES, INC.
USA OFFICE
Tel: +1-817-244-7777/1-8003 CSBUSA(272872)
Fax: +1-817-244-4445
E-mail: csb@csb-battery.com

CSB BATTERY LOGISTICS (SHANGHAI) CO., LTD.
SHANGHAI OFFICE
Tel: +86-21-5046-1622, 5046-0833
Fax: +86-21-5064-3314

CSB BATTERY LOGISTICS (SHANGHAI) CO., LTD.
BEIJING OFFICE
Tel: +86-10-6597-8060, 6597-8070
Fax: +86-10-6597-8050
E-mail: chinasisl@csb-battery.com